




BOOSTER CABLE SETS




PLUGS

#12-101

Standard - AN/2551 interchange, 3 pin (2 large, 1 small), fits most light aircraft (excluding some Beechcraft & Piper), solid brass terminals, durable hard wood body. 10 minutes to attach, no soldering required.

#12-301

Piper aircraft - round all metal body, brass terminal.



RECEPTACLES

#14-301

Piper aircraft - lite metal body, brass terminal.



#21-101

Standard - AN/2551 interchange plug, 3 pin (2 large, 1 small), fits most light aircraft (excluding some Beechcraft & Piper), solid brass terminals, durable hard wood body. 15 feet no. 4 extra flex twin cable with heavy duty.



#21-301

Piper aircraft, round all metal body, brass terminal, 15 feet no. 4 extra flex twin cable with heavy duty clamps.

IP-1430

RTV Sealant

RED, HI-TEMP

-75° TO 500° F

4.7 oz. TUB w/ Nozzle

MIL-A-46106

Type 1



SILICONE COMPOUND

- Same Application as DC-4
- Costs Less

INNERBOND COMPOUND Z-24

Serviceable temperature range

-40°F (-40°C) to 392°F (200°C).

Meets MIL-S-8660C. Seals and

protects electrical wiring

systems, cable connections,

terminals and sockets. Lubricant

for metal on rubber or plastic

surfaces.

© 2005 Trimcraft Aviation